

KAESER
KOMPRESSORER®



MODILAIR®-serien med CE-samsvar

Transportabel skruekompressor med verdensberømte SIGMA PROFILE ⚙️
Leveringsvolum 1,2 til 48,1 m³/min

www.kaeser.com

Alternative drivverk

			e-power		
Modell			M 13	M 17	M 13E
Volumstrøm ved drifts-trykk	7 bar	m³/min	1,2	–	1,25
	100 psi	cfm	42		44
	10 bar	m³/min	1,0	–	1,0
	145 psi	cfm	35		35
	13 bar	m³/min	0,85	–	0,85
	175 psi	cfm	30		30
	15 bar	m³/min	–	1,0	0,75
	200 psi	cfm		35	27
Maskin/motor			Honda GX 630	Honda GX 630	Siemens
Nominell effekt for maskin/motor		kW	15,5	15,5	7,5
Trykkluftbehandling			○	○	○



Kompakte maskiner

			e-power					
Modell			M 20	M 27	M 30	M 27E	M 31E	M 50E
Volumstrøm ved drifts-trykk	7 bar	m³/min	2,0	2,6	2,9	2,6	3,15	5,0
	100 psi	cfm	71	92	100	92	110	180
	10 bar	m³/min	–	2,1	–	–	2,6	3,8
	145 psi	cfm		74			92	135
	12 bar	m³/min	–	1,9	–	–	2,3	–
	175 psi	cfm		67			81	
	14 bar	m³/min	–	1,6	–	–	1,9	–
	200 psi	cfm		57			67	
Maskin/motor			Kubota D722	Kubota D1105	Kubota D1105	Siemens	Siemens	Siemens
Nominell effekt for maskin/motor		kW	14,7	18,2	18,2	15	22	25
Trykkluftbehandling			○	○	○	○	○	○
Alternativ for generator		kVA	–	6,5	–	–	–	–




Maksimal allsidighet

Modell			M 58utility	M 59	M 65	M 82
Volumstrøm ved drifts-trykk	7 bar	m³/min	5,1	5,5	6,6	8,4
	100 psi	cfm	180	195	230	295
	10 bar	m³/min	4,35	4,7	5,6	6,8
	145 psi	cfm	155	165	195	240
	12 bar	m³/min	–	–	–	6,1
	175 psi	cfm				215
	14 bar	m³/min	–	3,8	4,6	5,5
	200 psi	cfm		135	160	195
Maskin			Kubota V2403-CR	Hatz 3H50TICD	Kubota V2403CR-T	Kubota V3307-CR-T
Nominell effekt for maskin		kW	35,3	43,5	47,9	54,6
Trykkluftbehandling			○	○	○	○
Alternativ for generator		kVA	–	8,5 / 13	–	8,5 / 13



Effektpakker

Modell			M 125		M 171	
Volumstrøm ved drifts-trykk	8,6 bar	m³/min	–		17,0	
	125 psi	cfm			600	
	10 bar	m³/min	11,5		15,5	
	145 psi	cfm	405		550	
	12 bar	m³/min	10,7		13,5	
	175 psi	cfm	380		475	
	14 bar	m³/min	9,7		11,5	
	200 psi	cfm	345		405	
Maskin			Deutz TCD 4.1 L04		Deutz TCD 6.1 L06	
Nominell effekt for maskin		kW	105		129	
Trykkluftbehandling			○		○	
Alternativ for generator		kVA	13		–	



Store kompressorer

Store kompressorer				e-power		
Modell			M 255	M 250E	M 255E	
Volumstrøm ved drifts trykk	8,6 bar	m³/min	26,5	25,0	–	
	125 psi	cfm	950	885		
	10 bar	m³/min	24,8	20,4	24,7	
	145 psi	cfm	875	720	875	
	12 bar	m³/min	–	–	19,9	
	175 psi	cfm			705	
	14 bar	m³/min	19,7	16,2	–	
	200 psi	cfm	695	570		
Maskin/motor			Cummins B6.7	Siemens	Siemens	
Nominell effekt for maskin/motor			kW	210	132	160
Trykkluftbehandling			○	○	○	

